



### Water Pumps

Brand	Model	HP	RPM	Volt	Max Watts	Max Amps	HZ	GPH max	Cord Length (ft)	Warranty (Years)	Max Head (ft)	Min Head (ft)	Qmax/ Air Flow (L/Min)
Artesian 2 Low Head	A2-1/8-39	1/8	-	115/230	195	-	50/60	3900	6	3	17	3	246
	A2-1/4-47	1/4	-	115/230	290	-	50/60	4680	6	3	22	4	284
	A2-1/4-58	1/4	-	115/230	350	-	50/60	5760	6	3	23	5	344
	A2-1/3-63	1/3	-	115/230	450	-	50/60	6300	6	3	26	6	401
Artesian 2 High Flow	A2-1/2-76	1/2	-	115/230	600	-	50/60	7560	6	3	26	8	461
	A2-1/2-HF	1/2	-	115/208-230	950	4.1	60	-	6	3	-	3	477
	A2-3/4-HF	3/4	-	115/208-230	1180	5.2	60	8880	6	3	55	11	526
	A2-1-HF	1	-	115/208-230	1600	7	60	9840	6	3	65	13	625
	A2-1 1/2-HF	1 1/2	-	115/208-230	1990	8.8	60	11400	-	3	54	17	734
	A2-2-HF	2	-	230	2300	10	60	12840	-	3	55	20	803
Artesian Pro Low RPM	A2-3-HF	3	-	208-230	3200	14.2	60	14040	-	3	64	24	901
	AP 1/4-66	1/4	1725	115/230	370	-	50/60	6600	6	3	21	2	416
	AP 1/3-73	1/3	1725	115/230	460	-	50/60	7320	6	3	23	3	462
	AP 1/2-92	1/2	1725	115/230	620	-	50/60	9240	6	3	24	4	583
	AP 3/4-105	3/4	1725	115/230	830	-	50/60	10500	6	3	23	5	662
Artesian Pro High Flow	AP 1-120	1	1725	115/230	970	-	50/60	12000	6	3	24	6	757
	AP 1/2-HF	1/2	3450	115/208-230	930	4	60	8880	6	3	38	3	534
	AP 3/4-HF	3/4	3450	115/208-230	1130	5	60	10680	6	3	40	5	647
	AP 1-HF	1	3450	115/208-230	1530	6.8	60	13500	6	3	45	7	780
	AP 1 1/2-HF	1 1/2	3450	115/208-230	1940	8.5	60	13980	-	3	49	8	893
	AP 2-HF	2	3450	230	2450	10.7	60	15540	-	3	54	10	999
Artesian Pro	AP 3-HF	3	3450	208-230	3100	13.6	60	17820	-	3	58	13	1131
	AP 5-HF	5	3450	208-230	4000	17.6	60	19740	-	3	68	15	1249
Cascade High RPM	Dial-a-Flow	1/3-3	-	-	-	-	-	-	6	3	-	-	151-1173
	C1/3	1/3	3450	115/230	-	4	60	2370	6	3	56	3	150
	C1/2	1/2	3450	115/230	-	3.4	60	3570	6	3	71	7	225
	C3/4	3/4	3450	115/230	-	4.3	60	4818	6	3	79	12	304
	C1	1	3450	115/230	-	5.7	60	6240	6	3	81	11	394
	C1.5	1.5	3450	115/230	-	6	60	6720	-	3	80	16	424
Cascade Low RPM	C2	2	3450	115/230	-	8.6	60	8640	-	3	86	21	545
	C 1/8-22	1/8	1725	115/230	144	-	50/60	2260	6	3	16	4	132
	C 1/8-26	1/8	1725	115/230	167	-	50/60	2616	6	3	20	4	155
	C 1/8-36	1/8	1725	115/230	207	-	50/60	3612	6	3	16	7.5	227
Jebao	C 1/4-44	1/4	1725	115/230	290	-	50/60	4404	6	3	22	10	272
	C 1/4-49	1/4	1725	115/230	360	-	50/60	4944	6	3	23	13	303
Jebao	APP-2000	-	-	120	-	1.2	60	2000	28	-	16.4	-	126
	APP-3000	-	-	120	-	1.6	60	3000	28	-	19.7	-	189
	APP-4000	-	-	120	-	2.3	60	4000	28	-	21.3	-	252
	APP-6000	-	-	120	-	-	60	6000	28	-	24.6	-	379
	PF-2000	-	-	120/220	35	-	50/60	528	-	-	8.2	-	34
	PF-4000	-	-	120/220	75	-	50/60	1056	-	-	9.5	-	67
	PF-5000	-	-	120/220	98	-	50/60	1320	-	-	11.8	-	84
	SEP-20000	-	-	120	200	-	-	5250	-	-	-	-	367
SEP-30000	-	-	120	335	-	-	7925	-	-	-	-	500	
Wellspring	WS1/4-33	1/4	-	120	-	-	60	3420	18	2	20	1	196
	WS1/3-44	1/3	-	120	-	-	60	4800	18	2	27	3	258
	WS1/2-58	1/2	-	120	-	-	60	6420	18	2	36	4	321
	WS1-66	1	-	120	-	-	60	7260	18	2	46	5	378